

## SOLVENT BACKLIT FILM

<b>Film:</b>	220 micron Film
<b>Indoor Durability:</b>	2 year
<b>Applications:</b>	For backlighted signs, menu boards

### PHYSICAL PROPERTIES

PVC Film thickness (mm)	The table viewer in thickness	0.1±0.005
PVC Film Contraction tolerance	Stored at 25°C /65% RH	Single side contraction ≤ 2mm vertical side contraction ≤ 5mm (Within 15 days after film formed)
PET weight (g/m <sup>2</sup> )	Electronic balance	140±5
Adhesive thickness (µm)	The table viewer in thickness	20±2
Width tolerance (mm)	Band Tape	±2mm
Length tolerance (m)	Band Tape	±0.3m
Total weight (g/m <sup>2</sup> )	Electronic balance	300±10
Guarantee	1 year	

The technical data given in the Material Data Sheets are empirical values from current production and do not constitute any agreement concerning the nature and quality of goods. They refer to the goods supplied in the original state without any processing by the customer. The data are provided for information only and constitute just reference values. The customer is not released from conducting his own comprehensive tests concerning suitability for the use intended by the customer and any liability resulting from this before processing the product.  
Durability indicated is based on Asian conditions. Actual performance will be based on material preparation, substrate preparation, application, exposures and maintenance.